



### DIMENSIONS, ELECTRICAL & CAPACITY DATA

Unit Model	Compressor	BTUH @ 105°F Amb.	Unit MCA			Connections (In.)		Ship Weight (Lbs.)
			208- 230V/360	460V/3/60	575V/3/60	Liquid	Suction	
RCU 10A2	3DC3-100L	146.1	55.5	26.0	21.4	7/8	1 3/8	475
RCU 15A2	3DB3-150L	193	75.5	37.3	30.3	7/8	1 5/8	490
RCU 10H2	3DC3-100L	119.5	55.5	26.0	21.4	7/8	1 3/8	555
RCU 15H2	3DB3-150L	158.4	75.5	37.3	30.3	7/8	1 5/8	620
RCU 10M2 <sup>1</sup>	3DC3-100L	96.7	75.5	41.0	31.4	7/8	1 3/8	555
RCU 15M2 <sup>1</sup>	3DB3-150L	128	95.5	52.3	40.3	7/8	1 5/8	620
RCU 8L2 <sup>1</sup>	3DB3-075L	37.3	55.4	31.1	24.6	7/8	1 3/8	535
RCU 10L2 <sup>1</sup>	3DS3-100L	44.1	73.5	34.3	31.8	7/8	1 3/8	555
RCU 8L5 <sup>1</sup>	3DB3-075L	37.9	55.4	31.1	24.6	7/8	1 3/8	535
RCU 10L5 <sup>1</sup>	3DS3-100L	52.4	73.5	34.3	31.8	7/8	1 3/8	560

1. With evaporator power supply

Refrigerant charges are in lbs.; R22 for A2, H2, M2, L2 and R404A for L5

Capacities listed;  
 A2 @ +40°F SST  
 H2 @ +30°F SST  
 M2 @ +20°F SST  
 L2/L5 @ -20°F SST