



DIMENSIONS, ELECTRICAL & CAPACITY DATA

Unit Model	Compressor	Dimensions (In.)					BTUH ² @ 95°F Amb	Unit MCA ³			Connections		Ship Weight (Lbs.)
		L	W	H	A	C		208- 230V/3/60	460V/3/60	575V/3/60	Liquid	Suction	
ACU 5M2	2DC3-0500	80 3/8	40 1/4	44 1/2	42 15/16	38	38.7	47.5	25.2	21.4	5/8	1 3/8	1240
ACU 8M2	2DA3-0750	120 3/8	40 1/4	44 1/2	82 15/16	38	66.6	63.2	31.0	29.4	5/8	1 3/8	1395
ACU 10M2	3DB3-1000	120 3/8	40 1/4	44 1/2	82 15/16	38	94.3	82.7	43.4	33.4	7/8	1 3/8	1440
ACU 15M2	3DS3-1500	120 3/8	40 1/4	44 1/2	82 15/16	38	128.6	103.0	54.7	42.3	7/8	1 5/8	1560
ACU 20M2	4DA3-2000	164	48 1/4	57 1/2	109 9/16	55	136.7	123.0	64.2	47.1	7/8	1 5/8	1600
ACU 25M2	4DH3-2500	164	48 1/4	57 1/2	109 9/16	55	175.9	142	74.4	59.2	7/8	2 1/8	1870
ACU 30M2	4DJ3-3000	164	48 1/4	57 1/2	109 9/16	55	205.7	157	81.4	65.3	1 1/8	2 1/8	1960
ACU 35M2	6DH3-3500	229	48 1/4	57 1/2	162	55	251.0	190	97.8	77.0	1 1/8	2 1/8	2400
ACU 40M2	6DJ3-4000	229	48 1/4	57 1/2	162	55	310.0	233	119	90.8	1 1/8	2 1/8	2680
ACU 50M2 ¹	8DP1-5000	176	93 1/2	65 1/2	109 9/16	55	362.0	298	152	125	1 3/8	2 5/8	3200
ACU 50M2 ¹	8DS1-6000	176	93 1/2	65 1/2	109 9/16	55	422.0	358	184	137	1 3/8	3 1/8	3500

1. Duplex Units, 4 fans wide
 2. Capacity @ +20°F SST
 3. With evaporator power supply
- Refrigerant charges are in lbs. - R22